



# 3400mAh 0.46KWh Portable Lithium Battery Power Station For Golf Car Battery

#### **Basic Information**

Place of Origin: ChinaBrand Name: XWELL

• Certification: UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1

safety standard, CE, FCC, ROHS, battery

UN38.3, MSDS, UL, CB, BIS, PSE

Model Number: XW-600W-01

Minimum Order Quantity: 1 pcsPackaging Details: Carton

Delivery Time: 7-10 working days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

Supply Ability: 5000 pcs per month



#### **Product Specification**

USB1 Output: QC3.0 MAX 18 W 12V

Plenty Capacity: 0.46KWh

LCD: Battery Percentage Or Battery Column

Display

Battery Output: PD 100W Output

Ouput: 0.6KWCylcle Life: > 1000

• Input Power Supply: DC5521 12-24V-5Am, PD 100W

AC Output: AC220V/50Hz

• USB Output: 2 \* QC3.0 MAX 18 W 12V / 1.5A ; SCP

Maximum Output Power: Maximum 22.5W

• Batteries: LiFePO4 Battery / 3400mAh

Highlight: 3400mAh Portable Lithium Battery Power

Station

0.46KWh Portable Lithium Battery Power

Station

#### **Product Description**

#### High-Power Portable Lithium Battery Power Station Emergency Pc+V0 Flame Retardant Case Golf Car Battery

The biggest advantage of our product over other power stations is that it has UPS function. Connect the product between wall outlet and devices, when there is a sudden power failure, our power station will automatically switch to the UPS power supply mode within 10ms, so as to keep safe working for the computer, refrigerator, bottle warmer and other equipment below 600W.


#### **Features**

- 1. High power with cigar capacity
- 2. Support solar panel charging 12-24v
- Fully charged time: about 5-6h
- 3. 1W high brightness, with 2-level dimming and SOS flashing

#### Specification

| Category                          | Project                                       | Specifications   |
|-----------------------------------|---|--|
| INTPUT                            | DC input                                      | DC5521 12-24V-5A   |
|                                   | DC input                                      | PD 100W  |
| AC OUT 220V                       | AC output voltage                             | 1 port, AC220V±5%  |
|                                   | AC output power                               | 600W   |
|                                   | AC output over power protection               | 650W Approximately   |
|                                   | AC output waveform                            | pure sine wave   |
|                                   | AC output peak                                | 1200W Peak maintenance time <50ms  |
|                                   | frequency                                     | 50Hz   |
| USB output<br>port                | USB1 output                                   | QC3.0 MAX 18 W 12V / 1.5A ; SCP maximum output power: maximum 22.5W                        |
|                                   | USB2 output                                   | QC3.0 MAX 18 W 12V / 1.5A ; SCP maximum output power: maximum 22.5W                        |
|                                   | TYPE-C1 output                                | PD / QC3.0 MAX 30W 12V/2.5A  |
| DC12V output                      | DC1 DC2 output                                | 12V / 10A MAX  |
| TYPE-C output/input               | TYPE-C2                                       | PD 100W output   |
| Batteries                         | type  | LiFePO4 battery / 3400mAh  |
|                                   | capacity                                      | 23.8Ah (6S7P)  |
|                                   | power   | 460Wh  |
|                                   | cycle life                                    | 1000+ times  |
| Charging parameters               |   | DC 12-24V / 5A   |
| charging time                     | 5 - 6H  | Charge from 0% to 100% (automatic cut-off)   |
| Full voltage                      | 21.9V ±0.1V                                   | The voltage when the battery is charged to the automatic cut-off                           |
| LCD display                       | Display power; charging, stop charging status | Battery percentage and battery column display  |
|                                   | DC, AC, inverter status                       | The display shows  |
| boot static                       |   | <10W   |
| Protective function               |   | Short circuit, overload, over temperature, over voltage, over current, under voltage, etc. |
| over<br>temperature<br>protection | over temperature protection                   | ≥85  |
|                                   | over temperature recovery                     | ≤70  |

#### Front pannel



- 1 → DC12V/10A(DC5521) × 2 2 → USB QC3.0 × 2 3 → TYPE-C1 30W × 1 4 → TYPE-C2 PD100W I/O × 1 5 → AC ouput 220V/600W × 1
- 6 DC5521 12-24V/5A × 1
  7 Diplay screen × 1
  8 LED light × 1
  9 Switch × 5
  10 Car charger × 1

**Product accessories** 



### **Product Accessories**



Usage time for common devices





The use time data is for reference only.

Different equipment and use methods will lead different usage times.

#### Our services

- 1. Your inquiry related to our products price will be replied in 24 hours.
- 2. Experienced staffs to answer all your enquiries in fluent English
- 3. We make the OEM and ODM service for more than 5 years
- 4. Protection of your sales area, ideas of design and all your private information.
- 5. No matter big order or small order, we will provide all the best quality, best service.
- 6. If our products have any problem that we caused, they will be sent free in the next order.



## **XWELL** GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985

sales@esslithiumbattery.com esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China