

High-Capacity Lithium Batteries 2.56kwh to 10.24kwh 200A Empowering Your Needs

UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE

Basic Information

- Place of Origin:
- Brand Name: XWELL

China

7-10 working days

5000 pcs per month

MoneyGram

- Certification:
- Model Number: XW-SL15120
- Minimum Order Quantity: 1 pcs
- Packaging Details: Carton
- Delivery Time:
- Payment Terms: L/C, D/A, D/P, T/T, Western Union,
- Supply Ability:



Product Specification

- Nominal Capacity: 2.52kwh 5.12kwh 48V
- Nominal Voltage: 48V
- Operating Voltage Range:
- Rated Working Current: 100A
- Weight: 96.5kg
- 600*460*457mm • Dimension:
- Battery Cell Type: LiFePO4
- Communication CAN/RS485/RS232 AC110V/220V/50Hz/60Hzmethod:
- Highlight: 200A Lithium Batteries,
 - 10.24kwh Lithium Batteries. 2.56kwh Lithium Batteries

2.56kwh 5.12kwh 10.24kwh 200a Lithium Batterie Lifepo4 Lithium Battery For Solar Power Storage

ESS Lithium Battery Description

ESS Lithium Battery is a revolutionary power solution. With advanced technology and high-quality materials, it offers exceptional performance and reliability. The battery has a high energy density, providing long-lasting power for various applications. It is designed to be safe, durable, and environmentally friendly. Whether for residential, commercial, or industrial use, ESS Lithium Battery is the ideal choice for those seeking efficient and sustainable energy storage.

ESS Lithium Battery Features

High Energy Density: Having excellent energy density means that it can store more power under the same volume and weight to meet long time and high intensity power demand. Features

Long cycle life: After careful design and optimization, this product has a charge/discharge cycle life of up to thousands of times, which greatly reduces the frequency of battery replacement and maintenance costs.

Fast charging: Supporting fast charging technology, the battery can be fully charged in a short time, which greatly improves the usage efficiency.


Safe and stable: Built-in multiple safety protection measures, including overcharging, over-discharging, overheating, shortcircuit and other protection mechanisms, to ensure the safety of the use process.

Environmental protection and energy saving: Made of environmentally friendly materials, it is pollution-free, while the high efficiency of energy utilization also helps to reduce energy waste, in line with the concept of green development.

ESS Lithium Battery Specification

1 Module	2 Modules	3 Modules	4 Modules	5 Modules	6 Modules
5.12	10.24	15.36	20.48	25.6	30.72
48V					
96.5	151.5	206.5	261.5	316.5	371.5
48V					
600x460x	600x460x	600x460x	600x460x	600x460x	600x460x
457	637	817	997	1177	1357
LiFePO4					
CAN/RS485/RS232					
Charging: 0~45 Discharging: -10~50					
					IP55
Floor installation					
>6000 Cycles(80%DOD)					
100A					
					≤3.5%/month/@25°C
1S~6S					
	5.12 96.5 600x460x	5.12 10.24 96.5 151.5 600x460x 600x460x 457 637 Chargir	5.12 10.24 15.36 96.5 151.5 206.5 600x460x 600x460x 600x460x 457 637 817 LiFe CAN/RS4 Charging: 0~45 D IP Floor ins >6000 Cycle 10 ≤3.5%/mon	5.12 10.24 15.36 20.48 48∨ 96.5 151.5 206.5 261.5 48∨ 600x460x 600x460x 600x460x 457 637 817 997 LiFePO4 CAN/RS485/RS232 Charging: 0~45 Discharging: IP55 Floor installation >6000 Cycles(80%DOE 100A ≤3.5%/month/@25°C	48∨ 96.5 151.5 206.5 261.5 316.5 48∨ 600x460x 600x460x 600x460x 600x460x 457 637 817 997 1177 LiFePO4 CAN/RS485/RS232 Charging: 0~45 Discharging: -10~50 IP55 Floor installation >6000 Cycles(80%DOD) 100A ≤3.5%/month/@25°C

ESS Lithium Battery Connection Diagram



FAQ

1. Is the battery used in the battery pack grade A? Yes, we only use Grade A and Brand new cells inside.

2.Do you test and match the battery before installing the battery pack? Yes, every cell will be tested capacity, IR, voltage to surely match Voltage:The deviation less than 0.01V Resistance:The deviation less than 0.1m Ω Capacity: Same capacity matched

3. How do I store my batteries?

When the product is not in use for a long time, it should be stored in a dry, clean and well-ventilated warehouse at 10°C 35°C, avoiding inflammable and explosive materials; the battery pack should be charged and maintained regularly every three months to ensure that the battery best performance state.

4.What is the cycle life of the battery? 6000 cycle life @ 80% DOD

5.What's the warranty of your 48V/51.2V battery pack?

5 years warranty, if there is broken item under quality problem within warranty time, we will offer free replacements or refund, up to your needs

6.Do your batteries support series or parallel connection? Our 48V battery packs support up to 15pcs in parallel, if you need series connection, please contact our sales staff



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

€ +86 18620492985 Sales@esslithiumbattery.com € esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China